



The Clorox Company
1221 Broadway
Oakland, CA 94612
Tel. (510) 271-7000

Material Safety Data Sheet

I Product: CLOROX CLEAN-UP CLEANER WITH BLEACH		
Description: CLEAR, FAINT YELLOW LIQUID WITH CHARACTERISTIC BLEACH ODOR		
Other Designations	Distributor	Emergency Telephone Nos.
Clorox Clean-Up Clorox Clean-Up – Fresh Scent Clean-Up Dilutable	Clorox Sales Company 1221 Broadway Oakland, CA 94612	For Medical Emergencies call: (800) 446-1014 For Transportation Emergencies Chemtrac (800) 424-9300

II Health Hazard Data	III Hazardous Ingredients									
Moderate eye irritant. Mild to moderate skin irritant. Occasional clinical reports suggest a low potential for skin sensitization upon exaggerated exposure to sodium hypochlorite if skin damage (e.g., irritation) occurs during exposure. Routine clinical tests conducted on intact skin with this product found no sensitization in the test subjects. Exposure to vapor or mist may irritate eyes, nose, throat, lungs. Harmful if swallowed. May cause nausea and vomiting if swallowed. The following medical conditions may be aggravated by exposure to high concentrations of vapor or mist: heart conditions or chronic respiratory problems such as asthma, emphysema, chronic bronchitis or obstructive lung disease. Under normal consumer-use conditions, the likelihood of any adverse health effects is low. FIRST AID: EYE CONTACT: Remove any contact lenses, and flush eyes thoroughly with water for 15 minutes. If irritation persists, call a physician. SKIN CONTACT: Remove contaminated clothing; wash affected skin with water. IF BREATHING IS AFFECTED: Get fresh air immediately. IF SWALLOWED: Drink a glass of water. Call a physician.	<table><tr><th><u>Ingredient</u></th><th><u>Concentration</u></th><th><u>Worker Exposure Limit</u></th></tr><tr><td>Sodium hypochlorite CAS #7681-52-9</td><td>1-5%</td><td>none established</td></tr><tr><td>Sodium hydroxide CAS #1310-73-2</td><td>0.5-2%</td><td>2 mg/m³, Ceiling-TLV 2 mg/m³, Ceiling-Federal OSHA PEL</td></tr></table> TLV = Threshold Limit Value Source: ACGIH 1992-1993 PEL = Permissible Exposure Limit Source: OSHA None of the ingredients in this product are on the IARC, OSHA or NTP carcinogen lists.	<u>Ingredient</u>	<u>Concentration</u>	<u>Worker Exposure Limit</u>	Sodium hypochlorite CAS #7681-52-9	1-5%	none established	Sodium hydroxide CAS #1310-73-2	0.5-2%	2 mg/m ³ , Ceiling-TLV 2 mg/m ³ , Ceiling-Federal OSHA PEL
<u>Ingredient</u>	<u>Concentration</u>	<u>Worker Exposure Limit</u>								
Sodium hypochlorite CAS #7681-52-9	1-5%	none established								
Sodium hydroxide CAS #1310-73-2	0.5-2%	2 mg/m ³ , Ceiling-TLV 2 mg/m ³ , Ceiling-Federal OSHA PEL								

IV Special Protection and Precautions	V Transportation and Regulatory Data
Hygienic Practices: Do not get in eyes or on clothing. Avoid prolonged or repeated skin contact. Avoid prolonged breathing of vapor. Use only in well-ventilated areas. Personal Protection: Wear safety glasses. For sensitive skin or repeated/prolonged use, wear gloves. Ventilation: Use general ventilation to minimize exposure to gases or aerosols associated with this product.	U.S. DOT Hazard Class: Not restricted U.S. DOT Proper Shipping Name: Compound, cleaning, liquid EPA SARA TITLE III/CERCLA: This product contains no chemicals regulated under Section 313 and contains sodium hydroxide (CAS # 1310-73-2, <1%) which is regulated under Section 304/CERCLA. Packaged product may be regulated under Sections 311/312 of SARA Title III. TSCA - All chemicals in this product are listed on the TSCA Inventory

VI Spill Procedures/Waste Disposal	VII Reactivity Data
Spill Procedures: Absorb and containerize. Wash down residual to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material. Waste Disposal: Dispose of in accordance with all applicable federal, state, and local regulations.	Stable under normal use and storage conditions. Strong oxidizing agent. Reacts with other household chemicals such as toilet bowl cleaners, rust removers, acids or ammonia-containing products to produce hazardous gases, such as chlorine and other chlorinated compounds. Prolonged contact with metal or old porcelain may cause pitting or discoloration.

VIII Fire and Explosion Data	IX Physical Data
Flashpoint: greater than 200°F Fire Extinguishing Agents: Water spray, dry chemical or carbon dioxide (CO ₂). Special Fire-Fighting Procedures: None Unusual Fire and Explosion Hazards: None	Appearance: Clear, faint yellow liquid Odor: Characteristic bleach odor pH: 12.4 - 12.8 Solubility in water: Completely soluble Specific gravity (water = 1): 1.034 at 25 °C